

Micron Elite 2x2

Linear LED Centre Basket Troffer

CSA, cUL, cETL, or equal

Project Reference: _____ Fixture Type: _____ Cat. No.: _____ Voltage: _____ Options: _____



SPECIFICATIONS

- Shallow centre basket, low profile for easy installation, IC rated
- Ribbed white translucent diffuser for soft, even light and visual comfort
- High performance, DLC Premium listed,* modern styling
- Die-formed 24-gauge cold-rolled steel body
- Matte white, baked acrylic paint finish
- High reflectance white interior
- Fully recessed luminaire fits standard T-grid ceilings
- Field replaceable Seoul LED engine and Espen driver
- 0-10V dimmable, easy access plate for wiring
- 120-277V standard, available with 347V step-down transformer
- Rated life: over 100,000 hours per L70 TM-21 at 70°C

ORDERING INFORMATION

Product Code	Wattage	Lumens	Dimensions	CCT	CRI
MEP4-2X2-38L-40K-UNV	30W	3780 lm	23.8" x 23.8" x 2.8"	4000K	>80
MEP4-2X2-32L-40K-UNV*	26W	3250 lm	23.8" x 23.8" x 2.8"	4000K	>80
MEP4-2X2-44L-40K-UNV*	35W	4410 lm	23.8" x 23.8" x 2.8"	4000K	>80

***Special Order**

ACCESSORIES/OPTIONS

Product Code	Description
35K	3500K option: replace "40K" in product code above with "35K"
50K	5000K option: replace "40K" in product code above with "50K"
-SM	Add suffix "-SM" for surface mount shroud kit
-EM	Add suffix "-EM" for 90-minute emergency backup battery option

* Not all configurations are currently DLC listed, consult factory to confirm DLC status